

DEVICE FOR READING BIOCHIP

Publication number: JP2001194310

Publication date: 2001-07-19

Inventor: TANAAMI TAKEO, ICHIHARA AKIRA

Applicant: YOKOGAWA ELECTRIC CORP

Classification:

- **International:** C12M1/00; C12Q1/68; G01N21/55; G01N21/64; G01N21/78; G01N33/53; G01N33/543; G01N37/00; C12M1/00; C12Q1/68; G01N21/55; G01N21/64; G01N21/77; G01N33/53; G01N33/543; G01N37/00; (IPC-1:7) G01N21/78, C12M1/00, C12Q1/68, G01N21/64, G01N33/53, G01N33/543, G01N33/566

- **European:** G01N21/56B2; G01N21/64P

Application number: JP20000007725 20000117

Priority number(s): JP20000007725 20000117, EP20010105586 20010306, US20010798605 20010302


Also published as:

EP1239279 (A1)
US2002123132 (A1)
EP1239279 (B1)

[Report a data error here](#)

Abstract of JP2001194310

PROBLEM TO BE SOLVED: To realize a device for reading a biochip, capable of enhancing S/N and reducing a cost. **SOLUTION:** This device for reading the biochip is equipped with a light source, a lens for turning output light from the light source into parallel light, an excitation filter for transmitting the output light of specific wavelengths and outputting it as excited light, a photo detecting element for detecting fluorescence generated from a sample by the excited light, and an objective lens for condensing the fluorescence generated at a biochip where the sample is disposed to the detecting element. The excited light comes into the biochip at an angle larger than a critical angle to the biochip substrate.



Data supplied from the [esp@cenet](#) database - Worldwide